

TECHNICAL BULLETIN

CRYSTOLON[®] Kiln Furniture

CN-192

CN192 is a coarse-grained, oxide bonded silicon carbide composition that offers good thermal shock resistance and oxidation resistance. CN192 was developed for a variety of kiln furniture applications where a “dry” (minimally glazed) surface is desirable. It is commonly found in batt or plate configurations.

Typical Characteristics

Chemistry	%
SiC	88
SiO ₂	10
Fe ₂ O ₃	0.5
Other	1.5
Maximum Use Temperature*	
°C	1500
°F	2730
Bulk Density (g/cc)	2.6
Apparent Porosity (%)	18
Modulus of Rupture (psi)	
20°C (70°F)	4000
1250°C (2280°F)	5000
1450°C (2640°F)	3000
Thermal Conductivity (BTU-in / ft²-h-°F)	
315°C (600°F)	113
650°C (1200°F)	120
980°C (1800°F)	104
1150°C (2100°F)	100
Coefficient of Thermal Expansion	
30 - 1500°C	5.8 x 10 ⁻⁶ per °C
85 - 2730°F	3.2 x 10 ⁻⁶ per °F
Emissivity	0.92

*May be used at higher temperatures but with loss of strength and ability to resist oxidation. Date: 07/04

Supersedes: Rev. 03/01

1 New Bond Street • PO Box 15136 • Worcester, MA 01615-0136 • (508) 795-5577 • FAX: (508) 795-5011 • ISO9001:2000 Certified

The information contained in this document is believed to be accurate and reliable but is provided without guarantee or warranty on the part of Saint-Gobain Ceramics. Further, nothing present herein should be interpreted as an authorization or inducement to practice any patented invention without an appropriate license.
SGC Standard Terms and Conditions apply to all purchases.

Rev. 11/03